

3MP IP VIDEO SURVEILLANCE BULLET CAMERA



KEY FEATURES

- 3 Megapixel (2048 x 1536) High Resolution
- Records High Than 1080p
- True Day/Night Auto Switch
- IP66 Ingress Protection
- IR LED up to 30m
- Vandal-Proof Housing

| SPECIFICATIONS | |
|-----------------------------|---|
| CAMERA | |
| Image Sensor | 1/3" progressive scan CMOS |
| Min. Illumination | 0.028 lux @ F2.0 AGC ON 0 lux with IR |
| Shutter Time | 1/30s -1/100,000s |
| Lens | 4mm @ F2.0 |
| Lens Mount | M12 |
| Day & Night | IR Cut filter with audio switch |
| Digital Noise Reduction | 3D DNR |
| COMPRESSION STANDARD | |
| Video Compression | H.264 / MJPEG |
| Bit Rate | 32 Kbps ~ 16 Mbps |
| IMAGE | |
| Max Image Resolution | 2048 x 1536 |
| Frame Rate | 60 Hz: 30 fps (1280 x 960) 30 fps (1280 x 720) |
| Image Settings | Saturation, brightness, contrast, sharpness adjustable through client software or web browser |

For more information about this product, please contact us today by calling 1-877-888-8894.

3MP IP VIDEO SURVEILLANCE BULLET CAMERA



| SPECIFICATIONS | |
|-------------------------|---|
| NETWORK | |
| Network Storage | NAS |
| Alarm Trigger | Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception |
| Protocols | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos |
| Interoperability | ONVIF, PSIA, CGI |
| Security | User Authentication, watermark |
| INTERFACE | |
| Communication Interface | 1 RJ-45, 10M / 100M Ethernet Port |
| GENERAL | |
| Operating Condition | -30° C ~ 60° C (-22° F ~ 140° F) Humidity 90% or Less (non-condensing) |
| Power Supply | 12 VDC ± 10%, PoE (802.3af) |
| Power Consumption | Max. 4 W (ICR on Max. 5.5W) |
| IR Range | Up to 30 meters |
| Dimensions | 60.4 x 76.5 x 138.1mm |
| Weight | 300g |