

3MP IP VIDEO SURVEILLANCE DOME CAMERA



KEY FEATURES

- 3 Megapixel (2048 x 1536) High Resolution
- Records Higher Than 1080p
- True Day/Night Auto Switch
- IP66 Ingress Protection
- IR LED up to 30m
- Vandal-Proof Housing

SPECIFICATIONS

CAMERA

Image Sensor	1/3" progressive scan CMOS
Min. Illumination	0.028 lux @ F2.0 AGC ON 0 lux with IR
Shutter Time	1/30s - 1/100,000s
Lens	4mm@F2.0, angle of view: 52° (2.8mm, 6mm 12mm, optional)
Lens Mount	M12
Angle Adjustment (2-Axis)	Pan: 0° ~ 355°, tilt: 0° ~ 65°
Day & Night	ICR

COMPRESSION STANDARD

Video Compression	H.264 / MJPEG
Bit Rate	32 Kbps ~ 16 Mbps
Dual Stream	Yes

IMAGE

Max Image Resolution	2048 x 1536
Frame Rate	60 Hz: 30 fps (1280 x 960) 30 fps (1280 x 720)
Image Settings	Saturation, brightness, contrast adjustable through client software or web browser

For more information about this product, please contact us today by calling 1-877-888-8894.

3MP IP VIDEO SURVEILLANCE DOME CAMERA



SPECIFICATIONS	
NETWORK	
Network Storage	NAS
Alarm Trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System Compatibility	ONVIF, PSIA, CGI
General Functionality	Flickerless, heartbeat, mirror, user authentication, video mask, watermark
INTERFACE	
Communication Interface	1 RJ-45, 10M / 100M Ethernet Port
GENERAL	
Operating Condition	-30° C ~ 60° C (-22° F ~ 140° F) Humidity 90% or Less (non-condensing)
Power Supply	12 VDC ± 10%, PoE (802.3af)
Power Consumption	2 W ~ 4 W (IR LEDs: +2W)
Impact Protection	IEC60068-275Eh, 50J, EN50102, up to IK10
IR Range	Approximately 20 to 30 meters
Dimensions	140 x 92 mm
Weight	600g