# IP BASED SURVEILLANCE CAMERAS





#### FlexMount S15

- Weatherproof dual camera system (IP65) for flexible mounting solutions
- Two separately connected, discreet miniature sensor modules
- Image sensor and microphone integrated directly into the sensor module
- Double Hemispheric equipment replaces up to eight cameras
- Integrated DVR functionality: Slot for MicroSD card (up to 64 GB)
- Functional expansion via MiniUSB and MxBus connector



### **AllroundDual M15**

- Modular system with exchangeable image sensors
- Weatherproof premium dual camera for all kinds of applications (IP66)
- Combined day/night camera for 24-hour use
- 5MP sensors: 2.5 times more details compared to full HD
- Including video motion detection software Mx Activity Sensor



### AllroundMono M25

- Freely configurable lens: Telephoto/wide-angle lens, day/night, CSVario and hemispheric (180°)
- 5MP image sensor technology delivers excellent image quality
- installation on walls, poles or ceilings
- Integrated DVR (up to 64 GB) for HiRes video recording without affecting the network load
- Sturdy, low-maintenance and weatherproof from -30 to +50 °C (-22 to +122 °F) (IP 66)
- Digital, continuous panning, tilting, zooming
- Microphone, speaker and intelligent movement sensors

# IP BASED SURVEILLANCE CAMERAS





## **Hemispheric Q25**

- High-resolution widescreen panorama from wall to wall, ideal for access control
- Integrated DVR (up to 64 GB) for long-term recording without network load
- Digital continuous tilting, panning and zooming without mechanically moving the camera
- Robust and low maintenance with no moving parts
- 5MP sensor technology with up to 30 fps and improved zoom
- Microphone, speaker, MxBus and intelligent movement sensors
- Optimized image quality and reduced motion blur even in poor lighting conditions



#### **Dual Dome D15**

- individual choice of lenses: tele/wide-angle, day/night, panorama function
- integrated DVR (up to 64 GB) stores up to 520,000 HiRes images (6 days with 1 fps)
- only one network cable (data & power/PoE)
- continuous digital pan, tilt and zoom (virtual PTZ function)
- highest audio quality thanks to new codec and echo elimination
- optimized interfaces: MxBus and MiniUSB for e.g. UMTS and GPS
- robust, maintenance-free, IP65 weatherproof, from -30 to +60 °C (-22 to +140 °F)



### **IP Video Door Station T25**

- Two-way video around the world
- Allround view with no blind spots
- Recording with sound
- Keyless access
- Integrated message function