

NETWORK VIDEO RECORDER (NVR)



KEY FEATURES

- Third-party network supported
- Up to 5 Megapixels resolution recording
- HDMI / VGA output up to 1920 1080p
- HDD quota and group management
- 4 independent PoE network interfaces



Rear Panel

1. LAN network interface
2. RS-485 interface
3. 100-240VAC power input
4. Power switch
5. USB interface
6. GND
7. HDMI interface
8. VGA output
9. Audio input
10. Audio output
11. Network interface with PoE function

NVR SPECIFICATIONS

32-16-8-4 Channel IP Video Input

2-way audio input	32-ch BNC (2.0Vp-p, 1k) 16-8-4-ch RCA(2.0Vp-p, 1k)
-------------------	---

Video/Audio Output

VGA output	1-ch, resolution: 1920 x 1080p/60Hz
CVBS output	1-ch, BNC (1.0 Vp-p, 75) Resolution: 704 x 576 (PAL); 704 x 480 (NTSC)
HDMI output	1-ch, resolutions: 1920 x 1080p/60Hz
Recording resolution	5MP / 3MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF
Audio output	32-ch 2-ch BNC (Linear electrical level, 600) 16-8-4-ch 1-ch RCA (Linear, 1k)
Playback resolution	5MP / 3MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF
Synchronous playback	16-8-4-ch only
Hard Disk	
Interface type	32-ch 4 SATA plus DVD-RW 16-8-4-ch 2 SATA
Capacity	Up to 4TB for each disk
e-SATA interface	1 e-SATA interface

For more information about this product, please contact us today by calling 1-877-888-8894.

NETWORK VIDEO RECORDER (NVR)



NVR SPECIFICATIONS	
External Interface	
Network Interface	<p>32-ch 1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface 8 independent 100 Mbps PoE network interfaces</p> <p>16-8-4-ch 1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface 8 independent 10/100 Mbps PoE network interfaces 4 independent 10/100 Mbps PoE network interfaces</p>
Serial interfaces	<p>32-ch 1 RS-485 half-duplex interface</p> <p>16-8-4-ch 1 RS-485 interface (Reserved)</p>
USB interface	<p>32-ch 3 USB 2.0 interfaces</p> <p>16-8-4-ch 2 USB 2.0 interfaces</p>
Alarm in /out	16 / 4 (optional)
General	
Power supply	<p>32-ch 100-240VAC, 6.32A, 50-60Hz</p> <p>16-ch 12VDC</p> <p>8-4-ch 100-240VAC, 3A , 47~63Hz</p>
Consumption	<p>32-ch 45 Watt without hard disk or DVD-RW</p> <p>16-8-4-ch 15 Watt without hard disk</p>
Working temperature	-10 C ~ +55 C
Working humidity	10% ~ 90%
Chassis	<p>32-ch 19-inch rack-mounted, 1.5U chassis</p> <p>16-8-4-ch 19-inch rack-mounted, 1U chassis</p>
Dimension (W D H)	<p>32-ch 440 x 330 x 70mm, 16-8-4-ch 445 x 290 x 45mm</p>
Weight	2Kg (without hard disk)